=> IFW: Scan as Doc Code: SRNT <= Doc Date:

TC 3700 Inventor Search Program

See attached inventor searches for applications and/or patents to help resolve questions of overlapping subject matter. These searches are provided as an initial examination aid: examiners should perform updated or expanded PALM or EAST inventors searches as appropriate.

Serial Number: 10 705 509

1.) See <u>attached</u> printout of inventors listed in PALM

2.) See <u>attached</u> EAST Inventor Search Printout shows Inventor search terms

PALM INTRANET

Day: Tuesday Date: 7/31/2007

Time: 11:04:38

Inventor Information for 10/708509

| Inventor Name | City | State/Country |
|-----------------------------------|----------------------------|--------------------|
| SPARKS, DOUGLAS R | WHITEMORE LAKE | MICHIGAN |
| NAJAFI, NADER | ANN ARBOR | MICHIGAN |
| Appin Info Contents Petition Info | Atty/Agent Info Continuity | //Reexam Foreign I |
| Search Another: Application # | or Patent# | Search |
| PCT / | Search Search | |
| Attorney Docket # | Search | |

Search

To go back use Back button on your browser toolbar.

Back to PALM ASSIGNMENT OASIS Home page

Bar Code #

| • | | | | · | | | |
|-------------------------|--------------|----------|----|--|------------|---|----------------------------------|
| | | | | | | | • |
| JS 20070157739 A1 | US- PGPUB | 20070712 | 10 | MICROFLUIDIC DEVICE AND METHOD OF OPERATION | 73/861.352 | 137/2 | Sparks; Douglas Ray et al. |
| JS 20070151335 \1 | US- PGPUB | 20070705 | | MICROFLUIDIC DEVICE | 73/204.26 | 73/202 | Sparks; Douglas Ray et al. |
| JS 20070032734 \1 | US- PGPUB | 20070208 | | METHOD FOR MONITORING A PHYSIOLOGIC PARAMETER OF PATIENTS WITH CONGESTIVE | 600/513 | | Najafi, Nader et al |
| JS 20060213552 A1 | US- PGPUB | 20060928 | | HEART FAILURE FLUID SYSTEM AND METHOD OF ASSESSING A PROPERTY OF A FLUID FLOWING THEREIN | 137/2 | 123/445, 180/338, 184/6.21, 303/1, 60/276 | Sparks; Douglas Ray et al |
| JS 20060211981 \1 | US- PGPUB | 20060921 | | MEDICAL TREATMENT PROCEDURE AND SYSTEM IN WHICH BIDIRECTIONAL FLUID FLOW IS SENSED | 604/44 | 604/29; 604/6.09 | Sparks; Douglas Ray et al. |
| JS 20060175303 A1 | US- PGPUB | 20060810 | | PROCESS OF MAKING A MICROTUBE AND MICROFLUIDIC DEVICES FORMED THEREWITH | 219/121.43 | | Sparks, Douglas Ray et al. |
| JS 20060169038 \1 | US- PGPUB | 20060803 | | FLUID SENSING DEVICE WITH INTEGRATED BYPASS AND PROCESS THEREFOR | 73/202 | | Sparks, Douglas Ray et al |
| JS 20060047205 A1 | US- PGPUB | 20060302 | | DELIVERY METHOD AND SYSTEM FOR MONITORING CARDIOVASCULAR PRESSURES | 600/486 | | Ludomirsky, Achiau et al. |
| JS | US- | 20060223 | | PROCESS OF | 29/592.1 | 73/204.26; | Sparks; |

| 20060037187 | PGPUB | | MAKING A | | 73/861.351 | Douglas |
|--------------------------------|--------------|----------|---|------------|---|-------------------------------------|
| A1 | | | MICROTUBE AND MICROFLUIDIC DEVICES FORMED | | 737001.331 | Ray et al. |
| JS 20060010964 | US- PGPUB | 20060119 | THEREWITH Device and method for sensing rheological properties of a fluid | 73/54.01 | | Sparks; Douglas Ray et al. |
| A1 JS 20050284815 A1 | US- PGPUB | 20051229 | MEDICAL TREATMENT SYSTEM AND METHOD | 210/645 | 210/646; 210/742; 604/4.01; 604/65 | Sparks, Douglas Ray et al. |
| JS 20050235759 A1 | US- PGPUB | 20051027 | DRUG-SPECIFIC FLUID DELIVERY SYSTEM | 73/861.352 | | Sparks, Douglas Ray et al. |
| JS 20050126304 A1 | US- PGPUB | 20050616 | FLUID INFUSION METHOD AND SYSTEM THEREFOR | 73/861.05 | | Sparks, Douglas Ray et al. |
| JS 20050065589 X1 | US- PGPUB | 20050324 | Method and anchor for medical implant placement, and method of anchor manufacture | 607/126 | | Schneider, Richard Lee et al. |
| JS 20040255648 A1 | US- PGPUB | 20041223 | RESONANT TUBE VISCOSITY SENSING DEVICE | 73/54.41 | | Sparks, Douglas Ray |
| JS 20040171983 A1 | US- PGPUB | 20040902 | FLUID DELIVERY SYSTEM AND SENSING UNIT THEREFOR | 604/65 | 128/DIG.13 | Sparks, Douglas R et al |
| JS 20030,159741 \1 | US- PGPUB | 20030828 | FLUID DELIVERY SYSTEM AND METHOD | 137/814 | 604/67 | Sparks, Douglas Ray |
| JS 20030138656 A1 | US- PGPUB | 20030724 | Method of forming a reactive material and article formed thereby | 428/615 | 428/687 | Sparks, Douglas Ray |
| JS 20030121313 A1 | US- PGPUB | 20030703 | Micromachined fluid analysis device and method | 73/38 | | Sparks, Douglas Ray |
| JS 20030061889 A1 | US- PGPUB | 20030403 | Micromachined fluidic apparatus | 73/861.355 | 29/557; 29/890.14 | Tadigadapa, Srinivas et al. |
| JS 20020194908 \1 | US- PGPUB | 20021226 | Integrated microtube sensing device | 73/204.26 | | Sparks, Douglas Ray |

| , | | | | • | • | • |
|-------------------------------|--------------|----------|---|-----------|--|----------------------------------|
| | | | | • | | |
| JS 20020193818 V1 | US- PGPUB | 20021219 | Process of forming a microneedle and microneedle formed thereby | 606/185 | | Sparks, Douglas Ray |
| JS 20020185557 A1 | US- PGPUB | 20021212 | Micromachined lysing device and method for performing cell lysis | 241/1 | 241/2; 241/301 | Sparks, Douglas Ray |
| JS 20020151816 A1 | US- PGPUB | 20021017 | Wireless MEMS capacitive sensor for physiologic parameter measurement | 600/547 | | Rich, Colli A. et al. |
| JS 20020115920 A1 | US- PGPUB | 20020822 | MEMS capacitive sensor for physiologic parameter measurement | 600/345 | 600/485; 600/549 | Rich, Colli A. et al. |
| JS 7228735 32 | USPAT | 20070612 | Fluid sensing device with integrated bypass and process therefor | 73/204.26 | | Sparks; Douglas Ray et al. |
| JS 7211048 31 | USPAT | 20070501 | System for monitoring conduit obstruction | 600/508 | 600/481; 600/483; 600/485; 600/486; 607/126; 607/60 | Najafi; Nader et al |
| JS 7059176 32 | USPAT | 20060613 | Resonant tube viscosity sensing device | 73/54.41 | 73/54.01; 73/54.02 | Sparks, Douglas Ray |
| JS 6968743 32 | USPAT | 20051129 | Implantable sensing device for physiologic parameter measurement | 73/724 | | Rich, Colli A. et al. |
| JS 6942169 32 | USPAT . | 20050913 | Micromachined lysing device and method for performing cell lysis | 241/1 | 241/2, 241/301, 435/259, 435/820 | Sparks; Douglas Ray |
| JS 6935010 32 | USPAT | 20050830 | Method of fabricating a micromachined tube for fluid flow | 29/592.1 | | Tadigadapa Srinivas et al. |
| JS 6932114 ⁻ 32 | USPAT | 20050823 | Fluid delivery system and method | 137/814 | 604/67 | Sparks, Douglas Ray |
| JS 6926670 32 | USPAT | 20050809 | Wireless MEMS capacitive sensor for physiologic parameter measurement | 600/459 | | Rich; Colli A. et al. |
| JS 6923625 | USPAT | 20050802 | Method of forming a | 417/48 | 252/181.5; | Sparks, |

| 32 | | | | reactive material and | | 252/181.6; | Douglas |
|------------|----------|--------|----------|-----------------------------|------------|------------|---------------|
| 32 | | | | article formed thereby | | 257/682; | Ray |
| | | | [| article formed increasy | | 417/51; | |
| | | | | · | · | l ' | |
| | | | | | | 428/660; | |
| | | | | | | 428/666; | |
| | <u> </u> | | | | | 428/672 | |
| JS 6844213 | | USPAT | 20050118 | Process of forming a | 438/41 | 438/42; | Sparks; |
| 32 | | | | microneedle and | | 438/44; | Douglas |
| | | | | microneedle formed | | 438/53 | Ray |
| | | | 1. | thereby | | | |
| JS 6750521 | 1 | USPAT | 20040615 | Surface mount | 257/414 | | Chilcott; |
| 31 | | | | package for a | | , | Dan W. et |
| | | | | micromachined device | | | al. |
| IC ((47770 | - | LICDAT | 20031118 | | 73/204.26 | | _ |
| JS 6647778 | | USPAT | 20031118 | Integrated microtube | /3/204.20 | | Sparks, |
| 32 | | | | sensing device | | | Douglas |
| *** | ┞ | | | | | | Ray |
| JS 6637257 | | USPAT | 20031028 | Micromachined fluid | 73/38 | 422/101; | Sparks; |
| 32 | | | | analysis device and | | 422/255; | Douglas |
| • | 1 | | | method | | 422/267; | Ray |
| | | | | · | | 422/68.1; | |
| | | ļ | İ | | | 436/12; | |
| | | | | | | 436/14; | |
| | | |] | | | 436/15; | |
| | | | | • | · | 436/163; | |
| | | | . • | | | 436/177; | · |
| | | | } | · | | 436/177; | |
| | | | | · | | 73/61.63; | |
| | | | | | | 1 | • |
| 10.400054 | ┡ | | 20021221 | 26.1.1.6 | 72/702 | 73/61.71 | NT . C |
| JS 6499354 | | USPAT | 20021231 | Methods for | 73/723 | | Najafi; |
| 31 | | | | prevention, reduction, | | | Nader et al. |
| | | | | and elimination of | | | |
| | | | | outgassing and trapped | | | |
| | | | | gases in | | | |
| | | , | | micromachined | | i | |
| | | | | devices | | | |
| JS 6477901 | | USPAT | 20021112 | Micromachined fluidic | 73/861.352 | | Tadigadapa, |
| 31 | | | | apparatus | | | Srinivas et |
| 31 | İ | | ' | | | | al. |
| JS 6338284 | \vdash | USPAT | 20020115 | Electrical feedthrough | 73/866.1 | 216/2; | Najafi; |
| | | USIAI | 20020113 | structures for | /3/800.1 | 29/25.41; | Nader et al. |
| 31 | | | | micromachined | | ' | Ivauel et al. |
| | | | | | | 361/283.4; | <u> </u> |
| | | | | devices and methods | | 73/718; | |
| | _ | | | of fabricating the same | | 73/861.47 | |
| JS 6338010 | | USPAT | 20020108 | Multi-sensor module | 701/1 | 340/459; | Sparks; |
| 31 | | | | for communicating | | 701/33 | Douglas |
| | | | | sensor information | | | |

| • | | | | | | | | |
|------------|---|-------|----------|----|--|------------|---|----------------------------------|
| • • • | | | | | | | | |
| | | | | • | | | | |
| | | | | | over a vehicle data bus | | | |
| S 6140144 | | USPAT | 20001031 | | Method for packaging microsensors | 438/53 | 438/106; 438/108; 438/54 | Najafi, Nader et al |
| S 6062461 | | USPAT | 20000516 | | Process for bonding micromachined wafers using solder | 228/123.1 | 228/124.6; 228/174; 228/208 | Sparks; Douglas Ray et al. |
| S 6022756 | | USPAT | 20000208 | | Metal diaphragm sensor with polysilicon sensing elements and methods therefor | 438/53 | | Sparks; Douglas Ray et al. |
| S 5936164 | | USPAT | 19990810 | | All-silicon capacitive pressure sensor | 73/724 | | Sparks; Douglas Ray et al. |
| S 5932809 | | USPAT | 19990803 | | Sensor with silicon strain gage | 73/727 | 73/726 | Sparks; Douglas Ray et al. |
| S 5915281 | | USPAT | 19990622 | | Silicon force and displacement sensor | 73/862.581 | | Sparks; Douglas Ray |
| S 5831162 | | USPAT | 19981103 | | Silicon micromachined motion sensor and method of making | 73/504.12 | | Sparks; Douglas Ray et al. |
| S 5719069 | - | USPAT | 19980217 | | One-chip integrated sensor process | 438/50 | 148/DIG.135; 438/456; 438/52; 438/53 | Sparks; Douglas Ray |
| S 5706565 | | USPAT | 19980113 | | Method for making an all-silicon capacitive pressure sensor | 29/25.42 | | Sparks; Douglas Ray et al. |
| S 5663508 | | USPAT | 19970902 | | Silicon flow sensor | 73/861.71 | 73/861.74 | Sparks; Douglas Ray |
| S 5547093 | ļ | USPAT | 19960820 | | Method for forming a micromachine motion sensor | 438/52 | 216/2; 216/38 | Sparks; Douglas R. |
| S 5531121 | | USPAT | 19960702 | 14 | Micromachined integrated pressure sensor with oxide polysilicon cavity sealing | 73/716 | 257/E21.218; 257/E21.573; 73/720; 73/721 | Sparks; Douglas R. et al. |
| JS 5427975 | | USPAT | 19950627 | | Method of micromachining an integrated sensor on | 438/52 | 216/2; 257/E21.218; 257/E21.573; | Sparks; Douglas R. et al. |

.

| • | | : . | |
|-----------------|-------|----------|--|
| | | | |
| | | | the surface of a silicon wafer 438/53; 438/702; 438/739 |
| JS 5250837 \ | USPAT | 19931005 | Method for dielectrically isolating integrated circuits using doped oxide sidewalls 257/519 257/513; 257/517; Douglas R. 257/521; 257/622; 257/E21.551; 257/E21.571 |
| JS 5250461 \ | USPAT | 19931005 | Method for dielectrically isolating integrated circuits using doped oxide sidewalls 438/429 148/DIG.20; 257/E21.149; Douglas R. Douglas R. 257/E21.551; 438/360; 438/504; 438/973 257/E21.571; 438/973 438/973 |
| JS 5213999 \ | USPAT | 19930525 | Method of metal filled trench buried contacts 438/639 257/E21.158; 257/E21.295; 257/E21.396; 257/E21.537; 438/386; 438/678; 438/686 |
| JS 4732874 \ | USPAT | 19880322 | Removing metal precipitates from semiconductor devices |